

# Oil and Gas Specialty Rental



## Nitrogen Bundle Box

BB2000 HR/HP

2000 scfm @ 95-99% purity



*Atlas Copco*

# BB2000 HR/HP

Principal Data

General	
Dimensions LxWxH (mm/inches)	6.100 x 2.440 x 2.620 / 20 x 8 x 8.6
Mass (kg/lbs)	10.000 kg / 22.000 lbs

Required Feed Air	
Max. Pressure (PSI / bar)	350 PSI / 24 bar
Flow (scfm / m <sup>3</sup> /min)	3.550 scfm / 100 m <sup>3</sup> /min
Max. temp. (°C / °F)	55°C / 130°F
Aftercooler and water separator mandatory	

Discharge N <sub>2</sub>	
Flow	up to 2000 scfm
Purity	95-99%
Pressure	up to 340 PSI / 22 bar
Temperature	over ambient: +10 to 15°F / +6 to 9°C

Features	
Alarm	low purity
Nitrogen Flowmeter	measurement on discharge output
Air pretreatment	carbon tower; particulate filter; water separator; and coalescing filters
High Recovery membranes	up to 57% efficiency
Over Temperature protection	
Lifting	Forklift pockets, corner castings
Controls + connections	recessed panels
Auxiliary services required: Electrical supply for pre-heaters	3phase / 480V - 60Hz or 380V - 50Hz



environment



super silent



ease of use



safety

[www.atlascopco.com/rental](http://www.atlascopco.com/rental)

**Atlas Copco**