

# Atlas Copco Rental



## Ready for Crush?

To maintain a high level of productivity and quality you can rely on Atlas Copco Rental



- 100% Oil-free air compressors
- No oil in the air discharge
- EPA compliant and CARB permitted diesel units, low emission Tier 3 engines
- User friendly controls for easy operation
- 24/7 rental service, no hidden costs, we provide free routine maintenance
- A complete line of accessories including hoses, double wall fuel tanks, dryers, and nitrogen generation equipment

*Sustainable Productivity*

**Atlas Copco**

# Atlas Copco Rental

## Compressed Air Systems Electric and Diesel Driven

### Electric Driven Compressors

Auto-start feature for all units except PTMS 2300

Model	ZT55	ZT75	ZT145	PTSE 1050	PTSE 1600	PTSE 1600 MV**	PTMSE 2300**	PTMSE 1200	PET 925
Capacity (CFM)	300	400	650	1050	1600	1600	2300	1200	925
Oper. press. range (psig)	40-125	40-125	40-150	10-135	10-135	10-135	40-125	40-150	350-650
3 phase voltage/Hp	480/75	480/100	480/200	480/300	480/400	$\frac{2300-4160}{400}$	$\frac{2300-4160}{500}$	480/400	480/400
Starting AMPS *	247	330	660	895	1550	***	****	1150	1150
Loaded AMPS *	83	110	220	335	510	***	****	415	460
Overall length	10'0"	10'0"	10'6"	17'8"	17'8"	17'8"	18'10"	18'3"	48'
Overall height	9'0"	9'0"	9'0"	7'9"	7'9"	7'9"	9'4"	7'9"	12'6"
Overall width	5'6"	5'6"	5'10"	7'3"	7'3"	7'3"	7'11"	6'8"	8'5"
Shipping weight (WET)	6,560 lbs	7,260 lbs	9,700 lbs	15,000 lbs	15,000 lbs	15,000 lbs	24,350 lbs	15,000 lbs	54,000 lbs

\* All 480-575 volt units have Main Circuit Breakers, Soft Starters and TEFC Motors.  
 \*\* All Medium voltage units have Main Fuse over current protection, Full voltage Starters with TEFC Motors.  
 \*\*\* PTSE – 1600 medium voltage 2300 Volt Starting Amps 589 Loaded Amps 98, 4160 Volt Starting Amps 326 Loaded Amps 54.  
 \*\*\*\* PTMSE – 2300 Volt Starting Amps 679 Loaded Amps 108, 4160 Volt Starting Amps 390 Loaded Amps 62  
 575 volt units are available for Canada and USA.

### Diesel Driven Compressors

Model	PTS916	PTMS 2300	PNS1250 HIGH PRESSURE	TM2500 HIGH PRESSURE
Capacity (CFM)	1300-1600	2300	1250	2500
Oper. press. range (psig)	10-150	40-125	90-350	90-350
Fuel tank capacity (Gal)	237	322	237	474
Fuel consumed (Gal/Hr)	22	26.5	22	44
Overall length	17'8"	18'10"	17'8"	49'0"
Overall height	7'9"	9'4"	7'9"	11'3"
Overall width	7'3"	7'11"	7'3"	8'0"
Shipping weight (WET)	18,600 lbs	24,500 lbs	19,050 lbs	54,160 lbs



#### Reference Conditions

Absolute inlet pressure	14.7 psig
Air inlet temperature	68° F
Relative humidity	0%

Never use compressed air as breathing air without prior purification in accordance with local legislation and standards.

### Accessories

- Boosters
- Dryers
- Fuel Tanks (double wall)
- Hoses
- Manifolds
- Nitrogen Generation Equipment
- Particulate Discharge Scrubbers
- Trailers

### Triple certification, Triple benefit



24/7 Rental Service all across  
 USA and Canada  
 1-800-736-8267  
 www.AtlasCopcoRental.com

Atlas Copco