## **COMPRESSOR DATA SHEET**

## In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor: Variable Frequency Drive**

	MODEL DATA - FOR CO	<u> </u>	
1	Manufacturer: Atlas Copco		
	Model Number: G 160 VSD Pro W-10	Date:	02-20-2024
2	☐ Air-cooled ✓ Water-cooled	Туре:	Screw
		# of Stages:	1
3*	Full Load Operating Pressure*(b)	116.0	psig*(b)
4	Drive Motor Nominal Rating	214.6	hp
5	Drive Motor Nomnial Efficiency	96.3	percent
6	Fan Motor Nominal Rating (if applicable)	0.9	hp
7	Fan Motor Nominal Efficiency 40.6		percent
	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)
	191.9 Max	1,093.1	17.6
8*	159.7	925.1	17.3
	129.1	757.1	17.1
	100.1	589.1	17.0
	72.6 Min	421.0	17.2
9*	Total Package Input Power at Zero Flow*(c,d)	46.0	kW
10	Isentropic Efficiency	84.4	%
11	Specific Power (KW/100ACFM)  120  120  120  120  120  120  120  12	600 800 1000 Dacity (ACFM)	1200

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

Notes:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

Member

Volume Flow Rate			Specific Energy	No Load / Zero
at specified conditions		Volume Flow Rate	Consumption	Flow Power
<u>m3 / min</u>	<u>ft3 / min</u>	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	
0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3