	reueral Uniform			r Compressors Not Aj	ppilcable
		Rotary Con MODEL DATA -	pressor: Fix		
1	Manufacturer:	Atlas Copco	- 011 0 0		
	Model Number:	G 200 Pr	o-8.5	Date:	02-20-2024
2	Air-cooled	Water-co	oled	Type:	Screw
	✓ Oil-injected	Oil-free		# of Stages:	1
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			1,417.0	(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			123.0	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	123.3	psig*(c)
6	Drive Motor Nominal Rating			268.2	hp
7	Drive Motor Nominal Efficiency			95.8	percent
8	Fan Motor Nominal Rating (if applicable)		ole)	22.8	hp
9	Fan Motor Nominal Efficiency			89.5	percent
10*	Total Package Input	ge Input Power at Zero Flow*(e)		71.3	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			270.4	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			19.1	kW/100 cfm*(e)
	*For models that are tested in t	he CAGI Performance Ve	erification Progran	n, these items are verified by pro	ogram administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. www.cagi.org				
Member	 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report. 				
AGI sed Air & Gas Institute	 d. Total package input p e Tolerance is specified 	-	ed operating points as shown in table b	s will vary with control strategy elow:	
	Volume Flow Rate at specified conditions			Specific Energy	
	at specified of m3 / min	tt3 / min	Volume Flow	Rate Consumption %	Flow Power
	Below 0.5	Below 15 +		+/- 8	+/- 8 +/- 7 +/- 10
	0.5 to 1.5 15 to 50		+/- 6	+/- 7	
			+/- 5	+/- 6	
030.2			+/- 4	+/- 5	