	Federal Uniform			Air Compressors N	ot App	licable
		Rotary Con		1xea Speea IPRESSED AIR		
1	Manufacturer:	Atlas Copco	IORCON			
-	Model Number:	G 200 Pro	W-8.5	Γ	Date:	02-20-2024
2	Air-cooled	✔ Water-co	ooled	Т	ype:	Screw
	✓ Oil-injected	Oil-free		# of Sta	ges:	1
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		5	1,417.0		(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			123.0		psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		rre*(c)	123.3		psig*(c)
6	Drive Motor Nominal Rating			268.2		hp
7	Drive Motor Nominal Efficiency			95.8		percent
8	Fan Motor Nominal Rating (if applicable)		ble)	0.9		hp
9	Fan Motor Nominal Efficiency			40.6		percent
10*	Total Package Input	Total Package Input Power at Zero Flow*(e)		63.5		kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			262.6		kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			18.5		kW/100 cfm*(e)
	*For models that are tested in t	he CAGI Performance V	erification Prog	ram, these items are verified	l by progra	m administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.o a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.					
Member	 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, 					
AGI sed Air & Gas Institute	manufacturer may stad. Total package input pe Tolerance is specified	te "not significant" or "0 power at other than report 1 in ISO 1217, Annex E,)" on the test rep ted operating po as shown in tabl	ort. ints will vary with control s	-	
	Volume Flow Rate			Specific Energy		No Load / Zero
	at specified c <u>m3 / min</u>	tionditions <u>ft3 / min</u>	Volume F		-	Flow Power
	Below 0.5 Below 15		+/-		+/- 8	
	0.5 to 1.5 15 to 50 +/ 1.5 to 15 50 to 500 +/		+/-			+/- 10
			+/-	+/- 5 +/- 6		
030.2			+/-	4 +/-	+/- 5	