	Federal Unifor		SSOR DATA SH r Certain Air Co	IEET ompressors Not Aj	onlicable
			npressor: Fixed		spireusie
		MODEL DATA -	FOR COMPRE	CSSED AIR	
1	Manufacturer:	Atlas Copco			
	Model Number	G 250 Pr	ro-8.5	Date:	02-20-2024
2	Air-cooled	Water-co	ooled	Type:	Screw
	✓ Oil-injected	Oil-free		# of Stages:	1
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			1,572.3	(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			123.0	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	123.3	psig*(c)
6	Drive Motor Nominal Rating			335.3	hp
7	Drive Motor Nominal Efficiency			95.8	percent
8	Fan Motor Nominal Rating (if applicable)		ole)	22.8	hp
9	Fan Motor Nominal Efficiency			89.5	percent
10*	Total Package Input Power at Zero Flow*(e)		w*(e)	79.8	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			305.8	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			19.5	kW/100 cfm*(e)
3	For models that are tested in	the CAGI Performance V	erification Program, the	se items are verified by pro	ogram administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. www.cagi.org				
Member	 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, 				
AGI sed Air & Gas Institute	manufacturer may s d. Total package input e Tolerance is specifi	tate "not significant" or "0	" on the test report. ed operating points will as shown in table below	vary with control strategy.	,
	Volume Flow Rate			Specific Energy	No Load / Zero
	at specified		Volume Flow Rate	-	Flow Power
	<u>m3 / min</u> Balayy 0.5	<u>ft3 / min</u>	%	%	
	Below 0.5	Below 15	+/- 7	+/- 8	
	0.5 to 1.5	15 to 50	+/- 6 +/- 5	+/- 7	+/- 10
030.2	1.5 to 15 Above 15				
	11001015	110010 200	+/- 4	17-5	