

## **COMPRESSOR DATA SHEET**

## In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

**Rotary Compressor: Variable Frequency Drive** 

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer:	Atlas Copco					
	Model Number:	G110VSD-145-145	Date:	7/22/2020			
2	Air-cooled		Type:	Screw			
			# of Stages:				
3	Full Load Operating	Full Load Operating Pressure <sup>b</sup>		psig <sup>b</sup>			
4	Drive Motor Nomina	Drive Motor Nominal Rating		hp			
5	Drive Motor Nominal Efficiency		95	percent			
6	Fan Motor Nominal	Fan Motor Nominal Rating (if applicable)		hp			
7	Fan Motor Nominal	Fan Motor Nominal Efficiency		percent			
	Input Power (kW)		Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>			
	<b>127.5</b> Max		607.0	21.0			
Osk	105.9		506.0	20.9			
8*	83.5		403.0	20.7			
	62.6		297.0	21.1			
	41.8		191.0	21.9			
	<b>35.8</b> Min		160.0	22.4			
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>		0.0 77.44	kW			
10	Isentropic Efficiency	Isentropic Efficiency		%			
11	35.0 30.0 25.0 20.0 15.0						

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator.

Consult CAGI websitefor a list of participants in the third party verification program:

www.cagi.org

100.0

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.

200.0

300.0

**Capacity (ACFM)** 

Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35...

400.0

500.0

ACFM is actual cubic feet per minute at inlet conditions.

Member b. The operating pressure at which the Capacity (Item 8) and E

10.0

0.0

- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

NOTE: The terms power and energy are synonymous for purposes of this document.									
	Volume Flow Rate		Volume Flow Rate	Specific Energy	No Load / Zero Flow Power				
	at speci	fied conditions	volume flow Rate	Consumption	No Load / Zelo Flow Fowel				
	$\underline{m}^3 / \underline{\min}$	ft3 / min	%	%					
	Below 0.5	Below 17.6	+/- 7	+/- 8					
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%				
	1.5 to 15	53 to 529.7	+/- 5	+/- 6					
	Above 15	Above 529.7	+/- 4	+/- 5					

700.0

600.0

ROT 030.1

719 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.