

## **COMPRESSOR DATA SHEET**

## In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

**Rotary Compressor: Variable Frequency Drive** 

MODEL DATA - FOR COMPRESSED AIR									
1	Manufacturer:	Atlas Copco							
	Model Number:	G132VSD-145-138	Date:	7/22/2020					
2	<b>0</b> Air-cooled	Air-cooled		Screw					
			# of Stages:	1					
3	Full Load Operating Pressure <sup>b</sup>		138	psig <sup>b</sup>					
4	Drive Motor Nominal Rating		177	hp					
5	Drive Motor Nominal Efficiency		95	percent					
6	Fan Motor Nominal Rating (if applicable)		1.0	hp					
7	Fan Motor Nominal Efficiency		40.6	percent					
	Input Power (kW)		Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>					
	153.6 Max		741.0	20.7					
	121.5		597.0	20.4					
8*	96.2		476.0	20.2					
	70.8		353.0	20.1					
	47.0		229.0	20.5					
	47.0	<b>47.0</b> Min		20.5					
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>		0.0	kW					
10	Isentropic Efficiency		77.82	%					
11	Specific Power (kW/100 ACFM)  15	5.0 5.0 5.0 6.0 6.0 6.0 6.0 6.0 6.0 6.0 6.0 6.0 6	300.0 400.0 5 Capacity (ACFM)	00.0 600.0 700.0 800.0					
		No.	aph is only a visual representation of the	data in Section 9					

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program:

NOTES:

Member

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;

ACFM is actual cubic feet per minute at inlet conditions. b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.

- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

	me Flow Rate ified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m <sup>3</sup> /min	<u>ft3 / min</u>	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

