

## **COMPRESSOR DATA SHEET**

## In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

**Rotary Compressor: Variable Frequency Drive** 

MODEL DATA - FOR COMPRESSED AIR								
1	Manufacturer:	Atlas Copco						
	Model Number:	G160VSD-145-145	Date:	Date: 7/22/2020				
2	Air-cooled	X Water-cooled	Type:	Screw				
			# of Stages:	1				
3	Full Load Operating Pressure <sup>b</sup>		145	$psig^b$				
4	Drive Motor Nominal Rating		214	hp				
5	Drive Motor Nominal Efficiency		95	percent				
6	Fan Motor Nominal Rating (if applicable)		1.0	hp				
7	Fan Motor Nominal	Fan Motor Nominal Efficiency		percent				
	Input Power (kW)		Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>				
	179.0 Max		909.0	19.7				
0.14	154.4		791.0	19.5				
8*	114.1		588.0	19.4				
	76.1		382.0	19.9				
	58.2		277.0	21.0				
	58.2 Min		277.0	21.0				
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>		0.0	kW				
10	Isentropic Efficiency		82.79	%				
11	35.0 30.0 25.0 20.0 15.0 10.0 10.0 10.0 20.0 10.0 20.0 10.0 20.0 10.0							

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program:

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.

- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "nower" and "energy" are synonymous for purposes of this document

NOTE: The terms power and energy are synonymous for purposes of this document.									
	Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy	No Load / Zero Flow Power				
				Consumption					
	$\underline{m}^3 / \underline{\min}$	ft3 / min	%	%					
	Below 0.5	Below 17.6	+/- 7	+/- 8					
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%				
	1.5 to 15	53 to 529.7	+/- 5	+/- 6					
	Above 15	Above 529.7	+/- 4	+/- 5					

Note: Graph is only a visual representation of the data in Section  $\bf 8$ Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35...



Member

ROT 030.1

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.