



# COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

## MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: <b>Atlas Copco</b>		
2	Model Number: <b>G250VSD-145-102</b>	Date:	<b>7/22/2020</b>
	<input type="checkbox"/> Air-cooled <input checked="" type="checkbox"/> Water-cooled	Type:	<b>Screw</b>
		# of Stages:	<b>1</b>
3	Full Load Operating Pressure <sup>b</sup>	<b>102</b>	psig <sup>b</sup>
4	Drive Motor Nominal Rating	<b>268</b>	hp
5	Drive Motor Nominal Efficiency	<b>95</b>	percent
6	Fan Motor Nominal Rating (if applicable)	<b>1.0</b>	hp
7	Fan Motor Nominal Efficiency	<b>40.6</b>	percent
8*	Input Power (kW)	Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>
	<b>259.5</b> Max	<b>1477.0</b>	<b>17.6</b>
	<b>221.5</b>	<b>1294.0</b>	<b>17.1</b>
	<b>188.7</b>	<b>1124.0</b>	<b>16.8</b>
	<b>146.9</b>	<b>900.0</b>	<b>16.3</b>
	<b>107.4</b>	<b>672.0</b>	<b>16.0</b>
	<b>61.9</b> Min	<b>386.0</b>	<b>16.0</b>
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	<b>0.0</b>	kW
10	Isentropic Efficiency	<b>80.75</b>	%
11	<p>Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35...</p>		

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator.

Consult CAGI website for a list of participants in the third party verification program:

[www.cagi.org](http://www.cagi.org)

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$m^3 / min$	$ft^3 / min$	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	



ROT 030.1