

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer:	Atlas Copco					
	Model Number:	G250VSD-145-116	Date:	7/22/2020			
2	Air-cooled	① Air-cooled X Water-cooled Type: Screw		Screw			
			# of Stages:	1			
3	Full Load Operating Pressure ^b		116	psig ^b			
4	Drive Motor Nominal Rating		268	hp			
5	Drive Motor Nominal Efficiency		95	percent			
6	Fan Motor Nominal	Fan Motor Nominal Rating (if applicable)		hp			
7	Fan Motor Nominal	Fan Motor Nominal Efficiency		percent			
8*	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d			
	260.2 Max		1412.0	18.4			
	222.2		1234.0	18.0			
	199.8		1122.0	17.8			
	155.9		898.0	17.4			
	114.8		670.0	17.1			
	66.4 Min		385.0	17.2			
9*	Total Package Input	Total Package Input Power at Zero Flow ^{c, d}		kW			
10	Isentropic Efficiency	Isentropic Efficiency		%			
11	Specific Power (kW/100 ACFM) (kW/100 ACFM) 15	0 0 0					

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI websitefor a list of participants in the third party verification program:

200.0

0.0

NOTES:

Member

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.

400.0

600.0

800.0

Capacity (ACFM)

Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35...

1000.0

1200.0

1400.0

1600.0

- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

	ne Flow Rate fied conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft3 / min	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	



This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.