<mark>Itlas C</mark> a	COMPRESSOR DATA SHEET In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Fixed Speed						
MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Atlas Copco						
	Model Number: G250-123	Date:	7/22/2020				
2	XAir-cooled 0 Water-cooled	Туре:	Screw				
		# of Stages:	1				
3*	Rated Capacity at Full Load Operating Pressure ^{a, e}	1489	acfm ^{a,e}				
4	Full Load Operating Pressure ^b	123	psig ^b				
5	Maximum Full Flow Operating Pressure ^c	123	psig ^c				
6	Drive Motor Nominal Rating	335	hp				
7	Drive Motor Nominal Efficiency	95.0	percent				
8	Fan Motor Nominal Rating (if applicable)	10.7	hp				
9	Fan Motor Nominal Efficiency	89.9	percent				
10*	Total Package Input Power at Zero Flow ^e	75.3	kW ^e				
11	Total Package Input Power at Rated Capacity and Full281Load Operating Pressure ^d		kW^d				
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e	18.9	kW/100 cfm ^e				
13	Isentropic Efficiency	78.90	Percent				

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI websitefor a list of participants in the third party verification program: <u>www.cagi.org</u>

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.

Member

b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the



- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Compressed Air & Gas Institute	Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
	$\underline{m^3 / \min}$	<u>ft3 / min</u>	%	%	
	Below 0.5	Below 17.6	+/- 7	+/- 8]
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
ROT 030.1	1.5 to 15	53 to 529.7	+/- 5	+/- 6	
	Above 15	Above 529.7	+/- 4	+/- 5	
12/19 Rev 3 This form was developed	by the Compressed Air and Gas Ins	titute for the use of its members participat	ting in the PVP. CAGI has not inde	pendently verified the repor	ted data.