## **COMPRESSOR DATA SHEET**

## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Fixed Speed** 

Manufacturer: Atlas Copco  Model Number: GA 200-6.9  ✓ Air-cooled	Date: Type: # of Stages:	03-08-2022 Screw 1 (acfm) *(a,e)
✓ Air-cooled	Type: # of Stages:	Screw 1
Oil-injected Oil-free  ated Capacity at Full Load Operating essure*(a,e)	# of Stages:	1
ated Capacity at Full Load Operating essure*(a,e)		
essure*(a,e)	1,561.9	(acfm) *(a,e)
ıll I oad Operating Pressure*(b)		, , , , ,
in Loud Operating Pressure (b)	100.0	psig*(b)
aximum Full Flow Operating Pressure*(c)	107.3	psig*(c)
rive Motor Nominal Rating	147.5 & 147.5	hp
rive Motor Nominal Efficiency	95.4 & 95.4	percent
n Motor Nominal Rating (if applicable)	3.0 & 3.0 & 3.0	hp
n Motor Nominal Efficiency	79.9 & 79.9 & 79.9	percent
otal Package Input Power at Zero Flow*(e)	59.1	kW*(e)
otal Package Input Power at Rated Capacity d Full Load Operating Pressure*(d)	246.4	kW*(d)
pecific Package Input Power at Rated Capacity	15.8	kW/100 cfm*(e)
)1	tal Package Input Power at Zero Flow*(e)  tal Package Input Power at Rated Capacity d Full Load Operating Pressure*(d)  ecific Package Input Power at Rated Capacity d Full Load Operating Pressure*(e)	tal Package Input Power at Zero Flow*(e)  tal Package Input Power at Rated Capacity d Full Load Operating Pressure*(d)  246.4  ecific Package Input Power at Rated Capacity

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured

Member

- for this data sheet.

  c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume 1	Flow Rate		Specific Energy	No Load / Zero
at specified conditions		Volume Flow Rate	Consumption	Flow Power
<u>m3 / min</u>	<u>ft3 / min</u>	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	
0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 030.2

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

12/19 Rev 3