	Federal Uniform	Test Method fo Rotary Con		-	ssors Not Apj	plicable
MODEL DATA - FOR COMPRESSED AIR						
1	Manufacturer:	Atlas Copco				
	Model Number:	GA 315	5-6.9		Date:	03-08-2022
2	✓Air-cooled □Water-cooled		Type:		Screw	
	✓ Oil-injected	Oil-free		7	# of Stages:	1
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		2,210.1		(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			100.0		psig*(b)
5	Maximum Full Flow Operating Pressure*(c)			107.3		psig*(c)
6	Drive Motor Nominal Rating		214.6 & 214.6		hp	
7	Drive Motor Nominal Efficiency		96.2 & 96.2		percent	
8	Fan Motor Nominal Rating (if applicable)		4.0 & 4.0 & 4.0		hp	
9	Fan Motor Nominal Efficiency			79.9 & 79.9 & 79.9		percent
10*	Total Package Input F	Total Package Input Power at Zero Flow*(e)		87.3		kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			357.8		kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			16.2		kW/100 cfm*(e)
Notes: Member	<ul> <li>For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator</li> <li>Consult CAGI website for a list of participants in the third party verification program: www.cagi.org</li> <li>a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.</li> <li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li> </ul>					
AGI ed Air & Gas Institute	<ul><li>manufacturer may state</li><li>d. Total package input po</li><li>e Tolerance is specified</li></ul>	cordance with ISO 1217 e "not significant" or "0 wer at other than report in ISO 1217, Annex E, a wer" and "energy" are s	" on the test rep ted operating po as shown in tab	oort. vints will vary with le below:	n control strategy.	less than 1%,
	Volume Flow Rate		Specific Energy		No Load / Zero	
			Flow Rate Consumption		Flow Power	
	Below 0.5	Below 15	+/-		+/- 8	
	0.5 to 1.5	15 to 50		/- 6 +/- 7		+/- 10
	1.5 to 15			- 5 +/- 6		
)30.2	Above 15 Above 500 +		+/-	- 4 +/- 5		
-						