	Federal Unifor		SSOR DAT. r Certain A	A SHEE I .ir Compressors Not A	Applicable
		Rotary Con	-	-	
	1	MODEL DATA -	FOR COM	IPRESSED AIR	
1	Manufacturer:	Atlas Copco			
	Model Number	GA 315 V	V-10.4	Date	: 03-08-2022
2	Air-cooled	✓ Water-co	oled	Туре	: Screw
	✓ Oil-injected Oil-free			# of Stages	: 1
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			1,848.2	(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			150.0	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	158.1	psig*(c)
6	Drive Motor Nominal Rating			214.6 & 214.6	hp
7	Drive Motor Nominal Efficiency			96.2 & 96.2	percent
8	Fan Motor Nominal Rating (if applicable)		ole)	0.5	hp
9	Fan Motor Nominal Efficiency			31	percent
10*	Total Package Input	Cotal Package Input Power at Zero Flow*(e)		67.1	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			355.2	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			19.2	kW/100 cfm*(e)
,	*For models that are tested in	the CAGI Performance V	erification Progra	am, these items are verified by	program administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.				
Member	 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. 				
	c. No Load Power. In			easurement of no load power eq	uals less than 1%,
AU		tate "not significant" or "0 power at other than report	-	ort. nts will vary with control strates	27.
ed Air & Gas Institute	e Tolerance is specifie	ed in ISO 1217, Annex E, a	as shown in table	below:	
			ynonymous for p	ourposes of this document. Specific Ener	gy No Load / Zero
	Volume Flow Rate at specified conditions		Volume Flo	-	
	<u>m3 / min</u>	ft3 / min	%	%	
	Below 0.5	Below 15 +/			
	0.5 to 1.5	15 to 50	+/- (+/- 10
	1.5 to 15	50 to 500	+/- 5		1/- 10
030.2	Above 15				