

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Fixed Speed

| | MODEL DATA - FOR C | OMPRESSED AIF | R (Preliminary Da | ata) | |
|-----|--|-------------------------------|-------------------------------|--|--|
| 1 | Manufacturer: Atlas | Сорсо | | | |
| | Model Number: GA55+-100 AC | | Date: | 9/20/2023 | |
| 2 | X Air-cooled | Water-cooled | Type: | Screw | |
| | | | # of Stages: | 1 | |
| 3* | Rated Capacity at Full Load Opera | ting Pressure ^{a, e} | ressure ^{a, e} 408.8 | | |
| 4 | Full Load Operating Pressure ^b | | 100 | acfm ^{a,e} psig ^b | |
| 5 | Maximum Full Flow Operating Pro | essure ^c | 107 | psig ^c | |
| 6 | Drive Motor Nominal Rating | | 75 | hp | |
| 7 | Drive Motor Nominal Efficiency | | 94.5 | percent | |
| 8 | Fan Motor Nominal Rating (if app | licable) | 1.6 | hp | |
| 9 | Fan Motor Nominal Efficiency | | 88.5 | percent | |
| 10* | Total Package Input Power at Zero | Flow ^e | 13.2 | kW ^e | |
| 11 | Total Package Input Power at Rate Load Operating Pressure ^d | d Capacity and Full | 66.6 | kW^d | |
| 12* | Specific Package Input Power at R Full Load Operating Pressure ^e | ated Capacity and | 16.3 | kW/100 cfm ⁶ | |
| 13 | Isentropic Efficiency | | 81.57 | Percent | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI websitefor a list of participants in the third party verification program: www.cagi.org

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.

Member



- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

| Volume Flow Rate at specified conditions | | Volume Flow Rate | Consumption | Flow Power |
|---|--|--|--|---|
| $\underline{m^3 / \min}$ | <u>ft3 / min</u> | % | % | |
| Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | 1 |
| 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | +/- 10% |
| 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | |
| Above 15 | Above 529.7 | +/- 4 | +/- 5 | |
| | m3 / min Below 0.5 0.5 to 1.5 1.5 to 15 | $\underline{m^3 / \min}$ $\underline{ft3 / \min}$ Below 0.5 Below 17.6 0.5 to 1.5 17.6 to 53 1.5 to 15 53 to 529.7 | $\underline{m^3 / \min}$ $\underline{ft3 / \min}$ % Below 0.5 Below 17.6 +/- 7 0.5 to 1.5 17.6 to 53 +/- 6 1.5 to 15 53 to 529.7 +/- 5 | m³ / min ft3 / min % % Below 0.5 Below 17.6 +/- 7 +/- 8 0.5 to 1.5 17.6 to 53 +/- 6 +/- 7 1.5 to 15 53 to 529.7 +/- 5 +/- 6 |