

## **COMPRESSOR DATA SHEET**

## In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

**Rotary Compressor:** Fixed Speed

	MODEL DATA - FOR	COMPRESSED AII	R (Preliminary Da	ata)
1	Manufacturer: Atla	s Copco		
	Model Number: GA55+-175 AC		Date:	9/20/2023
2	X Air-cooled	Water-cooled	Type:	Screw
			# of Stages:	1
3*	Rated Capacity at Full Load Oper	rating Pressure <sup>a, e</sup>	305.2	acfm <sup>a,e</sup>
4	Full Load Operating Pressure <sup>b</sup>		175	psig <sup>b</sup>
5	Maximum Full Flow Operating P	ressure <sup>c</sup>	181	psig <sup>c</sup>
6	Drive Motor Nominal Rating		75	hp
7	Drive Motor Nominal Efficiency		94.5	percent
8	Fan Motor Nominal Rating (if ap	plicable)	1.6	hp
9	Fan Motor Nominal Efficiency		88.5	percent
10*	Total Package Input Power at Zen	ro Flow <sup>e</sup>	10.9	kW <sup>e</sup>
11	Total Package Input Power at Rat Load Operating Pressure <sup>d</sup>	ed Capacity and Full	68	$\mathrm{kW}^\mathrm{d}$
12*	Specific Package Input Power at Full Load Operating Pressure <sup>e</sup>	Rated Capacity and	22.3	kW/100 cfm
13	Isentropic Efficiency		80.36	Percent

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI websitefor a list of participants in the third party verification program: www.cagi.org

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.





- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:
  - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Consumption	Flow Power
$\underline{m^3 / \min}$	<u>ft3 / min</u>	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	1
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	
	m3 / min  Below 0.5  0.5 to 1.5  1.5 to 15	$\underline{m^3 / \min}$ $\underline{ft3 / \min}$ Below 0.5         Below 17.6           0.5 to 1.5         17.6 to 53           1.5 to 15         53 to 529.7	$\underline{m^3 / \min}$ $\underline{ft3 / \min}$ %           Below 0.5         Below 17.6         +/- 7           0.5 to 1.5         17.6 to 53         +/- 6           1.5 to 15         53 to 529.7         +/- 5	m³ / min         ft3 / min         %         %           Below 0.5         Below 17.6         +/- 7         +/- 8           0.5 to 1.5         17.6 to 53         +/- 6         +/- 7           1.5 to 15         53 to 529.7         +/- 5         +/- 6