

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Atlas Copco														
2	Model Number: GA 132 VSDs W-8.6	Date:	09-04-2025												
	<input type="checkbox"/> Air-cooled <input checked="" type="checkbox"/> Water-cooled	Type:	Screw												
		# of Stages:	1												
3*	Full Load Operating Pressure*(b)	125.0	psig*(b)												
4	Drive Motor Nominal Rating	177.0	hp												
5	Drive Motor Nominal Efficiency	96.3	percent												
6	Fan Motor Nominal Rating (if applicable)	0.5	hp												
7	Fan Motor Nominal Efficiency	31.0	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	155.2 Max	881.0	17.6												
	124.6	711.8	17.5												
	95.6	542.6	17.6												
	68.1	373.3	18.2												
	41.6 Min	204.1	20.4												
9*	Total Package Input Power at Zero Flow*(c,d)	0.0	kW												
10	Isentropic Efficiency	84.9	%												
11	<table border="1"> <caption>Graph Data: Specific Power vs Capacity</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr> <td>200</td> <td>20.5</td> </tr> <tr> <td>373.3</td> <td>18.2</td> </tr> <tr> <td>542.6</td> <td>17.6</td> </tr> <tr> <td>711.8</td> <td>17.5</td> </tr> <tr> <td>881.0</td> <td>17.6</td> </tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	200	20.5	373.3	18.2	542.6	17.6	711.8	17.5	881.0	17.6
Capacity (ACFM)	Specific Power (kW/100ACFM)														
200	20.5														
373.3	18.2														
542.6	17.6														
711.8	17.5														
881.0	17.6														

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.