

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

MODEL DATA - FOR COMPRESSED AIR						
1	Manufacturer: At	las Copco				
	Model Number: G	A55+-125	Date:	6/29/2020		
2	X Air-cooled	Water-cooled	Туре:	Screw		
			# of Stages:	1		
3*	Rated Capacity at Full Load Operating Pressure ^{a, e}		354.4	acfm ^{a,e}		
4	Full Load Operating Pressure ^b		125	psig ^b		
5	Maximum Full Flow Operating Pressure ^c		132	psig ^c		
6	Drive Motor Nominal Rating		75	hp		
7	Drive Motor Nominal Efficiency		94.2	percent		
8	Fan Motor Nominal Rating (if applicable)		2.4	hp		
9	Fan Motor Nominal Efficiency		76.0	percent		
10*	Total Package Input Power at Z	ero Flow ^e	16.8	kW ^e		
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		65.8	kW^{d}		
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e		18.6	kW/100 cfm ^e		
13	Isentropic Efficiency		80.90	Percent		

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI websitefor a list of participants in the third party verification program: www.cagi.org

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.





- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
 c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:
 - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Compressed Air & Gas Institute	Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
	$\underline{m}^3 / \underline{min}$	<u>ft3 / min</u>	%	%	
	Below 0.5	Below 17.6	+/- 7	+/- 8	1
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
ROT 030.1	1.5 to 15	53 to 529.7	+/- 5	+/- 6	
	Above 15	Above 529.7	+/- 4	+/- 5	