COMPRESSOR DATA SHEET In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors				
-	1	Manufacturer: Atlas Copco		
		Model Number: GA 90 +-10.4	Date:	06-29-2020
	2	✓ Air-cooled Water-cooled	Type:	Screw
			# of Stages:	1
	3*	Rated Capacity at Full Load Operating Pressure*(a,e)	502.4	(acfm) *(a,e)
-	4*	Full Load Operating Pressure*(b)	155.0	psig*(b)
	5	Maximum Full Flow Operating Pressure*(c)	158.1	psig*(c)
	6	Drive Motor Nominal Rating	120.7	hp
	7	Drive Motor Nominal Efficiency	96.2	percent
	8	Fan Motor Nominal Rating (if applicable)	5.9	hp
-	9	Fan Motor Nominal Efficiency	83.0	percent
-	10*	Total Package Input Power at Zero Flow*(e)	20.2	kW*(e)
	11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)	100.5	kW*(d)
	12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)	20.0	kW/100 cfm*(e)
ŀ				

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

13

Isentropic Efficiency

a. Measured at the discharge terminal point of the compressor package in accordance with Notes:

ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. Member The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured b. for this data sheet. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, c. manufacturer may state "not significant" or "0" on the test report. d. Total package input power at other than reported operating points will vary with control strategy. Compressed Air & Gas Institut Tolerance is specified in ISO 1217, Annex E, as shown in table below: e NOTE: The terms "power" and "energy" are synonymous for purposes of this document. Volume Flow Rate Specific Energy No Load / Zero Volume Flow Rate Flow Power at specified conditions Consumption <u>m3 / min</u> % % <u>ft3 / min</u> Below 0.5 Below 15 +/- 7 +/- 8 +/- 7 0.5 to 1.5 15 to 50 +/- 6 +/- 10 1.5 to 15 50 to 500 +/- 5 +/- 6 ROT 030.1 Above 15 Above 500 +/- 4 +/- 5 12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

84.1

Percent

www.cagi.org