

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Atlas Copco														
2	Model Number: ZR 200 VSD+-10.4	Date:	12-18-2024												
	<input type="checkbox"/> Air-cooled <input checked="" type="checkbox"/> Water-cooled	Type:	Screw												
	<input type="checkbox"/> Lubricated <input checked="" type="checkbox"/> Oil-free	# of Stages:	2												
3	Full Load Operating Pressure*(b)	150.0	psig*(b)												
4	Drive Motor Nominal Rating	134.1 & 134.1	hp												
5	Drive Motor Nominal Efficiency	97.3 & 97.3	percent												
6	Fan Motor Nominal Rating (if applicable)	--	hp												
7	Fan Motor Nominal Efficiency	--	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	212.7 Max	1,125.1	18.9												
	183.8	954.0	19.3												
	155.4	783.0	19.8												
	127.2	611.9	20.8												
	98.9 Min	440.9	22.4												
9*	Total Package Input Power at Zero Flow*(c,d)	0.0	kW												
10	<table border="1"> <caption>Graph Data Points</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr> <td>450</td> <td>22.5</td> </tr> <tr> <td>600</td> <td>21.0</td> </tr> <tr> <td>780</td> <td>20.0</td> </tr> <tr> <td>950</td> <td>19.5</td> </tr> <tr> <td>1100</td> <td>19.0</td> </tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	450	22.5	600	21.0	780	20.0	950	19.5	1100	19.0
Capacity (ACFM)	Specific Power (kW/100ACFM)														
450	22.5														
600	21.0														
780	20.0														
950	19.5														
1100	19.0														

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	