	Federal Unifor		SSOR DATA or Certain A	A SHEET ir Compressors Not A	pplicable	
		Rotary Cor	npressor: Fi	xed Speed		
	1	MODEL DATA -	FOR COM	PRESSED AIR		
1	Manufacturer:	Atlas Copco				
	Model Number	: ZT 37	-7.5	Date:	01-05-2024	
2	Air-cooled	Water-co	ooled	Type:	Tooth	
	Oil-injected Oil-free			# of Stages:	2	
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			201.5	(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			108.8	psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)			108.8	psig*(c)	
6	Drive Motor Nominal Rating			49.6	hp	
7	Drive Motor Nominal Efficiency			94.1	percent	
8	Fan Motor Nominal Rating (if applicable)		ble)	1.3	hp	
9	Fan Motor Nominal Efficiency			73	percent	
10*	Total Package Input Power at Zero Flow*(e)		ow*(e)	10.7	kW*(e)	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			46.1	kW*(d)	
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			22.9	kW/100 cfm*(e)	
3	For models that are tested ir	the CAGI Performance V	erification Progra	m, these items are verified by pr	ogram administrator	
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.c a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.					
Member	 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. 					
VU	c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.					
AUI ssed Air & Gas Institute	d. Total package inpute Tolerance is specifi	power at other than repor ed in ISO 1217, Annex E,	ted operating poin as shown in table	ts will vary with control strategy below:	<i>r</i> .	
Sector Sector	NOTE: The terms "power" and "energy" are synonymous fo Volume Flow Rate		synonymous for p	Specific Energ	y No Load / Zero	
	at specified conditions		Volume Flo			
	<u>m3 / min</u>	<u>ft3 / min</u>	%	%		
	Below 0.5 Below 15		+/- 7		+/- 10	
	0.5 to 1.5 15 to 50		+/- 6			
030.2	1.5 to 15 Above 15	1.5 to 15 50 to 500 +/ Above 15 Above 500 +/				
	1001015	110010 300	+/- 4	1/- 5	l	