	Federal Unifor	m Test Method for	SOR DATA S r Certain Air (pressor: Fixed	Compressors Not A	pplicable
		MODEL DATA -	-	-	
1	Manufacturer:	Atlas Copco			
	Model Number	ZR 200	-8.6	Date:	01-08-2021
2	Air-cooled	✔ Water-co	oled	Type:	Screw
	Oil-injected	✔ Oil-free		# of Stages:	2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			1,099.9	(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			102.0	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	124.8	psig*(c)
6	Drive Motor Nominal Rating			250.8	hp
7	Drive Motor Nominal Efficiency			94.0	percent
8	Fan Motor Nominal Rating (if applicable)		ole)		hp
9	Fan Motor Nominal Efficiency				percent
10*	Total Package Input Power at Zero Flow*(e)		w*(e)	36.5	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			186.1	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			16.9	kW/100 cfm*(e)
	*For models that are tested in	the CAGI Performance Ve	erification Program, t	hese items are verified by pro	ogram administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. www.cagi.org				
Member	 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report. 				
AUI sed Air & Gas Institute	 d. Total package input e Tolerance is specified 	-	ed operating points was shown in table belo		
	Volume Flow Rate at specified conditions V		Volume Flow R	Specific Energy	V No Load / Zero Flow Power
	<u>m3 / min</u>	<u>ft3 / min</u>	volume Flow R	ate Consumption	Flow rower
	Below 0.5	Below 15	+/- 7	+/- 8	
	0.5 to 1.5			-/- 6 +/- 7	+/- 10
			+/- 5	+/- 6	
030.2			+/- 4	+/- 5	