	Federal Unifor	m Test Method fo		Compressors Not A	pplicable
		Rotary Con MODEL DATA -	npressor: Fix FOR COMP	-	
1	Manufacturer:	Atlas Copco			
	Model Number		5-9	Date:	01-04-2021
2	Air-cooled	✓ Water-co	ooled	Type:	Screw
	Oil-injected	Oil-injected Oil-free		# of Stages:	2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			423.9	(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			117.0	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	130.5	psig*(c)
6	Drive Motor Nominal Rating			100.6	hp
7	Drive Motor Nominal Efficiency			94.1	percent
8	Fan Motor Nominal Rating (if applicable)		ole)		hp
9	Fan Motor Nominal Efficiency				percent
10*	Total Package Inpu	nput Power at Zero Flow*(e)		21.1	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			88.1	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			20.8	kW/100 cfm*(e)
,	For models that are tested in	the CAGI Performance V	erification Program	, these items are verified by pr	ogram administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program:       www.cagi.org         a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.       www.cagi.org				
Member	<ul> <li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li> <li>c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.</li> </ul>				
d Air & Gas Institute	<ul> <li>d. Total package input</li> <li>e Tolerance is specifi</li> </ul>	0	ed operating points as shown in table b	will vary with control strategy elow:	ι.
	Volume Flow Rate			Specific Energ	y No Load / Zero
	at specified		Volume Flow	1	Flow Power
	<u>m3 / min</u> Palaw 0.5	<u>ft3 / min</u> Balaw 15	% +/- 7	% +/- 8	
	Below 0.5 0.5 to 1.5				- / 10
	1.5 to 15	15 to 50	+/- 6 +/- 5	+/- /	+/- 10
30.2			+/- 3		
			· · · ·		L