	Federal Unifor	COMPRES m Test Method for Rotary Com	r Certain A	ir Compressors No	ot Applica	ble
		MODEL DATA -	<u> </u>	-		
1	Manufacturer:	Atlas Copco				
	Model Number	ZR 160	-8.6	Da	ate:	01-05-2024
2	Air-cooled	✔ Water-co	oled	Ту	pe:	Screw
	Oil-injected	✔ Oil-free		# of Stag	ges:	2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			911.3	(	acfm) *(a,e)
4	Full Load Operating Pressure*(b)			124.7		psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	124.7		psig*(c)
6	Drive Motor Nominal Rating			201.2		hp
7	Drive Motor Nominal Efficiency			96.5		percent
8	Fan Motor Nominal Rating (if applicable)		ole)			hp
9	Fan Motor Nominal Efficiency					percent
10*	Total Package Input Power at Zero Flow*(e)		w*(e)	29.6		kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			166.4		kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			18.3	kV	V/100 cfm*(e)
	*For models that are tested in	the CAGI Performance Ve	erification Progr	am, these items are verified	by program ad	ministrator
Notes:	Consult CAGI website for a list of participants in the third party verification program:       www.cagi.org         a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.       www.cagi.org					
Member	<ul> <li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li> <li>c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.</li> </ul>					
AUI ssed Air & Gas Institute	<ul><li>d. Total package input</li><li>e Tolerance is specific</li></ul>	-	ed operating points shown in table	nts will vary with control str below:	ategy.	
	Volume Flow Rate at specified conditions		V-L- El		Specific Energy No	
	at specified <u>m3 / min</u>	<u>ft3 / min</u>	Volume Fle	ow Rate Consum	puon	Flow Power
	Below 0.5	Below 15	+/- '		3	
	0.5 to 1.5         15 to 50         +/           1.5 to 15         50 to 500         +/			+/- 6 +/- 7 +/- 5 +/- 6		+/- 10
			+/- :			
030.2			+/- 4	4 +/- 5	+/- 5	