|                                | rederal Uniform  |                        |   | ir Compressors Not A                      | ррпсавіе            |
|--------------------------------|--|------------------------|---|---|---------------------|
|                                |  | MODEL DATA -           | npressor: Fi<br>FOR COM                 |   |                     |
| 1                              | Manufacturer:  | Atlas Copco            | 10110011                                |   |                     |
|                                | Model Number:  | ZR 275                 | 5-8.6                                   | Date:                                     | 01-05-2024          |
| 2                              | Air-cooled   | ✔ Water-co             | ooled                                   | Type:                                     | Screw               |
|                                | Oil-injected   | ✓ Oil-free             |   | # of Stages:                              | 2                   |
| 3*                             | Rated Capacity at Full Load Operating<br>Pressure*(a,e)  |                        | 5                                       | 1,550.5                                   | (acfm) *(a,e)       |
| 4                              | Full Load Operating Pressure*(b)   |                        |   | 124.7                                     | psig*(b)            |
| 5                              | Maximum Full Flow Operating Pressure*(c)   |                        | re*(c)                                  | 124.7                                     | psig*(c)            |
| 6                              | Drive Motor Nominal Rating   |                        |   | 348.7                                     | hp                  |
| 7                              | Drive Motor Nominal Efficiency   |                        |   | 96.2                                      | percent             |
| 8                              | Fan Motor Nominal Rating (if applicable)   |                        | ole)                                    |   | hp                  |
| 9                              | Fan Motor Nominal Efficiency   |                        |   |   | percent             |
| 10*                            | Total Package Input Power at Zero Flow*(e)   |                        | ow*(e)                                  | 53.2                                      | kW*(e)              |
| 11                             | Total Package Input Power at Rated Capacity<br>and Full Load Operating Pressure*(d)  |                        |   | 286.6                                     | kW*(d)              |
| 12*                            | Specific Package Input Power at Rated Capacity<br>and Full Load Operating Pressure*(e)   |                        |   | 18.5                                      | kW/100 cfm*(e)      |
|                                | *For models that are tested in   | the CAGI Performance V | erification Program                     | m, these items are verified by pr         | ogram administrator |
| Notes:                         | Consult CAGI website for a list of participants in the third party verification program: www.cagi.or<br>a. Measured at the discharge terminal point of the compressor package in accordance with<br>ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.   |                        |   |   |                     |
| Member                         | <ul> <li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li> <li>c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.</li> </ul> |                        |   |   |                     |
| AGI<br>sed Air & Gas Institute | <ul> <li>d. Total package input p</li> <li>e Tolerance is specifie</li> </ul>  | -                      | ted operating poin<br>as shown in table | ts will vary with control strategy below: |                     |
|                                | Volume Flow Rate<br>at specified conditions Volum  |                        | ¥7.1 E1                                 | Specific Energ                            |                     |
|                                | m3 / min   | <u>ft3 / min</u>       | Volume Flow                             | w Rate Consumption %                      | Flow Power          |
|                                | Below 0.5  |                        |   | +/- 8                                     | +/- 10              |
|                                | 0.5 to 1.5         15 to 50         +/           1.5 to 15         50 to 500         +/  |                        | +/- 6                                   | +/- 6 +/- 7                               |                     |
|                                |  |                        | +/- 5                                   | +/- 6                                     |                     |
| 030.2                          |  |                        | +/- 4                                   | +/- 5                                     |                     |