	Federal Uniform			Air Compressors N	ot Appli	cable
		Rotary Cor	-	-		
		MODEL DATA -	FORCOM	APRESSED AIR		
1	Manufacturer:	Atlas Copco				
	Model Number:	ZR 90 ST	D-10.4	D	ate:	01-05-2024
2	Air-cooled	✔ Water-co	ooled	T	ype:	Screw
	Oil-injected	✔ Oil-free		# of Sta	ges:	2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			510.3		(acfm) *(a,e)
4	Full Load Operating Pressure*(b)		150.0		psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)			150.8		psig*(c)
6	Drive Motor Nominal Rating			120.7		hp
7	Drive Motor Nominal Efficiency		96.2		percent	
8	Fan Motor Nominal Rating (if applicable)				hp	
9	Fan Motor Nominal Efficiency				percent	
10*	Total Package Input Power at Zero Flow*(e)		ow*(e)	20.3		kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			106.1		kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			20.8	1	kW/100 cfm*(e)
	*For models that are tested in	the CAGI Performance V	erification Prog	ram, these items are verified	by program	administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured					
Member	for this data sheet. c. No Load Power. In		7, Annex E, if n	neasurement of no load power		
ed Air & Gas Institute	<ul><li>d. Total package input</li><li>e Tolerance is specifie</li></ul>	power at other than repor d in ISO 1217, Annex E,	ted operating po as shown in tab	ints will vary with control st	rategy.	
	Volume Flow Rate			Specific	Energy	No Load / Zero
	at specified conditions		Volume F		Consumption	
	<u>m3 / min</u> Below 0.5	<u>ft3 / min</u> Palaw 15	% +/			-
	Below 0.5	Below 15	+/-		+/- 8 +/- 7	1/ 10
	0.5 to 1.5					+/- 10
030.2	<u>├</u> /		+/-		+/- 6 +/- 5	
	Above 15	Above 500	+/-	4 +/-	5	