COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Fixed Speed

MODEL DATA - FOR COMPRESSED AIR								
1	Manufacturer: Atlas Copco							
	Model Number: ZR 55 STD-10.4	Date:	01-05-2021					
2	☐ Air-cooled ✓ Water-cooled	Type:	Screw					
	☐ Oil-injected ✓ Oil-free	# of Stages:	2					
3*	Rated Capacity at Full Load Operating Pressure*(a,e)	302.8	(acfm) *(a,e)					
4	Full Load Operating Pressure*(b)	131.0	psig*(b)					
5	Maximum Full Flow Operating Pressure*(c)	150.8	psig*(c)					
6	Drive Motor Nominal Rating	73.8	hp					
7	Drive Motor Nominal Efficiency	95.8	percent					
8	Fan Motor Nominal Rating (if applicable)		hp					
9	Fan Motor Nominal Efficiency		percent					
10*	Total Package Input Power at Zero Flow*(e)	11.2	kW*(e)					
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)	62.6	kW*(d)					
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)	20.7	kW/100 cfm*(e)					

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Note

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- Member
- The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.



- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- i. Total package input power at other than reported operating points will vary with control strategy.
- e Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

	Volume l	Flow Rate		Specific Energy	No Load / Zero				
	at specified conditions		Volume Flow Rate	Consumption	Flow Power				
	<u>m3 / min</u>	<u>ft3 / min</u>	%	%					
	Below 0.5	Below 15	+/- 7	+/- 8					
	0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10				
	1.5 to 15	50 to 500	+/- 5	+/- 6					
	Above 15	Above 500	+/- 4	+/- 5					

ROT 030.2

12/19 Rev 3

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.