	Federal Unifor	m Test Method fo Rotary Con		Air Compressors	Not App	licable
		MODEL DATA -	-	_	1	
1	Manufacturer:	Atlas Copco				
	Model Number:	ZR 145 ST	D-10.4		Date:	08-10-2021
2	Air-cooled	✔ Water-co	oled		Туре:	Screw
	Oil-injected	✓ Oil-free		# of \$	Stages:	2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		756.5		(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			150.0		psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	150.8		psig*(c)
6	Drive Motor Nominal Rating		220.0		hp	
7	Drive Motor Nominal Efficiency		95.8		percent	
8	Fan Motor Nominal Rating (if applicable)		ole)			hp
9	Fan Motor Nominal Efficiency					percent
10*	Total Package Input Power at Zero Flow*(e)		w*(e)	24.1		kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			156.3		kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			20.7		kW/100 cfm*(e)
	*For models that are tested in	the CAGI Performance V	erification Prog	ram, these items are veri	fied by progra	am administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org   a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. www.cagi.org					
Member	<li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li>					
AGI ted Air & Gas Institute	<ul><li>manufacturer may st</li><li>d. Total package input</li><li>e Tolerance is specifie</li></ul>	accordance with ISO 1217 ate "not significant" or "0 power at other than report d in ISO 1217, Annex E, i power" and "energy" are s	" on the test rep ed operating po as shown in tab	ort. ints will vary with contr le below:	ol strategy.	ess than 1%,
	Volume Flow Rate			Specific Energy		No Load / Zero
	at specified conditions		Volume F		sumption	Flow Power
	<u>m3 / min</u> Below 0.5	<u>ft3 / min</u> Below 15	% +/-		% +/- 8	_
	0.5 to 1.5			- 6 +/- 7		+/- 10
	1.5 to 15 50 to 500 +/			+/- 5 +/- 6		
030.2			4 +/- 5		7	