	Federal Unifor	m Test Method fo		compressors Not A	pplicable	
		Rotary Con MODEL DATA -	npressor: Fixed FOR COMPR			
1	Manufacturer:	Atlas Copco				
	Model Number:	ZT 160	-8.6	Date:	01-08-2021	
2	Air-cooled	Water-co	ooled	Type:	Screw	
	Oil-injected	✓ Oil-free		# of Stages:	2	
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			883.6	(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			102.0	psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	124.8	psig*(c)	
6	Drive Motor Nominal Rating			201.2	hp	
7	Drive Motor Nominal Efficiency			93.6	percent	
8	Fan Motor Nominal Rating (if applicable)		ole)	10.7	hp	
9	Fan Motor Nominal Efficiency			81.3	percent	
10*	Total Package Input Power at Zero Flow*(e)		w*(e)	37.2	kW*(e)	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			161.5	kW*(d)	
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			18.3	kW/100 cfm*(e)	
	*For models that are tested in	the CAGI Performance V	erification Program, th	ese items are verified by pro	gram administrator	
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. www.cagi.org b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured					
AGI	for this data sheet. c. No Load Power. In manufacturer may st	accordance with ISO 1217 ate "not significant" or "0	7, Annex E, if measure " on the test report.	Consumption (Item 11) wer ment of no load power equa ll vary with control strategy.	ls less than 1%,	
ssed Air & Gas Institute	e Tolerance is specifie	ed in ISO 1217, Annex E, power" and "energy" are s	as shown in table below	v:		
	Volume Flow Rate at specified conditions		Volum - El P	Specific Energy		
	at specified <u>m3 / min</u>	<u>ft3 / min</u>	Volume Flow Ra %	te Consumption	Flow Power	
	Below 0.5	Below 15	+/- 7	+/- 8		
	0.5 to 1.5			+/- 7	+/- 10	
			+/- 5	+/- 6		
030.2			+/- 4	+/- 5		