	reuerar Onnorn		npressor: Fix	r Compressors Not Aj ed Speed	ppiicable
	Π	MODEL DATA -			
1	Manufacturer:	Atlas Copco			
	Model Number:	ZT 275	5-8.6	Date:	08-11-2021
2	Air-cooled	Water-co	ooled	Type:	Screw
	Oil-injected	✓ Oil-free		# of Stages:	2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		5	1,526.0	(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			124.7	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	124.7	psig*(c)
6	Drive Motor Nominal Rating			348.7	hp
7	Drive Motor Nominal Efficiency			94.9	percent
8	Fan Motor Nominal Rating (if applicable)		ole)	10.7	hp
9	Fan Motor Nominal Efficiency			81.3	percent
10*	Total Package Input Power at Zero Flow*(e)		ow*(e)	63.7	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			305.2	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			20.0	kW/100 cfm*(e)
	*For models that are tested in t	he CAGI Performance V	erification Program	n, these items are verified by pro	gram administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.or a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.				
Member	 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, measurement of the second power equals less than 1%, measurement of the second power equals less than 1%. 				
AUI sed Air & Gas Institute	 manufacturer may state "not significant" or "0" on the test report. d. Total package input power at other than reported operating points will vary with control strategy. e Tolerance is specified in ISO 1217, Annex E, as shown in table below: NOTE: The terms "power" and "energy" are synonymous for purposes of this document. 				
	Volume Flow Rate			Specific Energy	
	at specified c <u>m3 / min</u>	tt3 / min	Volume Flow	7 Rate Consumption %	Flow Power
	Below 0.5	Below 15	+/- 7	+/- 8	
	0.5 to 1.5 15 to 50 +/ 1.5 to 15 50 to 500 +/		+/- 6	+/- 7	+/- 10
			+/- 5	+/- 6	
030.2			+/- 4	+/- 5	