

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

| 1 | Manufacturer: Atlas Copco | | | | | | | | | | | | | | |
|-----------------|---|------------------------|----------------------------------|-----------------|-----------------------------|----|------|-----|------|-----|------|-----|------|-----|------|
| 2 | Model Number: ZT 30 FLX-8.6 VSD | Date: 03-18-2025 | | | | | | | | | | | | | |
| | <input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled | Type: Tooth | | | | | | | | | | | | | |
| | <input type="checkbox"/> Lubricated <input checked="" type="checkbox"/> Oil-free | # of Stages: 2 | | | | | | | | | | | | | |
| 3 | Full Load Operating Pressure*(b) | 124.7 | psig*(b) | | | | | | | | | | | | |
| 4 | Drive Motor Nominal Rating | 40.2 & 40.2 | hp | | | | | | | | | | | | |
| 5 | Drive Motor Nominal Efficiency | 96.3 & 96.3 | percent | | | | | | | | | | | | |
| 6 | Fan Motor Nominal Rating (if applicable) | 1.3 | hp | | | | | | | | | | | | |
| 7 | Fan Motor Nominal Efficiency | 54.0 | percent | | | | | | | | | | | | |
| 8* | Input Power (kW) | Capacity (acfm) *(a,d) | Specific Power (kW/100 acfm)*(d) | | | | | | | | | | | | |
| | 35.5 Max | 155.5 | 22.8 | | | | | | | | | | | | |
| | 31.4 | 135.5 | 23.1 | | | | | | | | | | | | |
| | 26.6 | 115.4 | 23.1 | | | | | | | | | | | | |
| | 23.2 | 95.3 | 24.4 | | | | | | | | | | | | |
| 9* | Total Package Input Power at Zero Flow*(c,d) | 0.0 | kW | | | | | | | | | | | | |
| 10 | <table border="1" style="margin: 10px auto; border-collapse: collapse;"> <caption>Data points from Specific Power vs Capacity graph</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr><td>75</td><td>26.5</td></tr> <tr><td>105</td><td>24.5</td></tr> <tr><td>120</td><td>23.5</td></tr> <tr><td>140</td><td>23.5</td></tr> <tr><td>155</td><td>23.0</td></tr> </tbody> </table> | | | Capacity (ACFM) | Specific Power (kW/100ACFM) | 75 | 26.5 | 105 | 24.5 | 120 | 23.5 | 140 | 23.5 | 155 | 23.0 |
| Capacity (ACFM) | Specific Power (kW/100ACFM) | | | | | | | | | | | | | | |
| 75 | 26.5 | | | | | | | | | | | | | | |
| 105 | 24.5 | | | | | | | | | | | | | | |
| 120 | 23.5 | | | | | | | | | | | | | | |
| 140 | 23.5 | | | | | | | | | | | | | | |
| 155 | 23.0 | | | | | | | | | | | | | | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member



| Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|-----------------------|------------------|-----------------------------|---------------------------|
| m ³ / min | ft ³ / min | % | % | |
| Below 0.5 | Below 15 | +/- 7 | +/- 8 | +/- 10 |
| 0.5 to 1.5 | 15 to 50 | +/- 6 | +/- 7 | |
| 1.5 to 15 | 50 to 500 | +/- 5 | +/- 6 | |
| Above 15 | Above 500 | +/- 4 | +/- 5 | |