

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Atlas Copco														
2	Model Number: ZT 45 FLX-10 VSD	Date:	03-18-2025												
	<input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled	Type:	Tooth												
	<input type="checkbox"/> Lubricated <input checked="" type="checkbox"/> Oil-free	# of Stages:	2												
3	Full Load Operating Pressure*(b)	145.0	psig*(b)												
4	Drive Motor Nominal Rating	40.2 & 40.2	hp												
5	Drive Motor Nominal Efficiency	96.3 & 96.3	percent												
6	Fan Motor Nominal Rating (if applicable)	2.6	hp												
7	Fan Motor Nominal Efficiency	59.0	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	49.6 Max	201.8	24.6												
	41.4	169.7	24.4												
	34.9	137.7	25.3												
	27.2	105.6	25.8												
9*	21.3 Min	73.6	28.9												
	Total Package Input Power at Zero Flow*(c,d)	0.0	kW												
10	<table border="1"> <caption>Graph Data</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr> <td>70</td> <td>29.0</td> </tr> <tr> <td>105.6</td> <td>25.8</td> </tr> <tr> <td>137.7</td> <td>25.3</td> </tr> <tr> <td>169.7</td> <td>24.4</td> </tr> <tr> <td>201.8</td> <td>24.6</td> </tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	70	29.0	105.6	25.8	137.7	25.3	169.7	24.4	201.8	24.6
Capacity (ACFM)	Specific Power (kW/100ACFM)														
70	29.0														
105.6	25.8														
137.7	25.3														
169.7	24.4														
201.8	24.6														

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	+/- 10
Below 0.5	Below 15	+/- 7	+/- 8	
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	