	Federal Uniform	n Test Method fo Rotary Cor		-	ot Appl	icable	
	ľ	-	_	IPRESSED AIR			
1	Manufacturer:	Atlas Copco					
	Model Number:	ZT 55 ST	ГD-8.6	D	ate:	07-22-2021	
2	Air-cooled	✓ Air-cooled			/pe:	Screw	
	Oil-injected	✓ Oil-free		# of Sta	ges:	2	
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		335.7		(acfm) *(a,e)		
4	Full Load Operating Pressure*(b)			124.7		psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)		ure*(c)	124.7		psig*(c)	
6	Drive Motor Nominal Rating			73.8		hp	
7	Drive Motor Nominal Efficiency			95.8		percent	
8	Fan Motor Nominal Rating (if applicable)		ble)	0.0		hp	
9	Fan Motor Nominal Efficiency			91.7		percent	
10*	Total Package Input	Total Package Input Power at Zero Flow*(		19.2		kW*(e)	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			72.8		kW*(d)	
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			21.7		kW/100 cfm*(e)	
	*For models that are tested in t	he CAGI Performance V	verification Prog	ram, these items are verified	by program	n administrator	
Notes:	Consult CAGI website for a list of participants in the third party verification program:       www.cagi.c         a.       Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.       www.cagi.c						
Member	<ul><li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li><li>c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,</li></ul>						
<b>AGI</b> sed Air & Gas Institute	<ul> <li>d. Total package input p</li> <li>e Tolerance is specified</li> </ul>	in ISO 1217, Annex E,	ted operating po as shown in tab	ints will vary with control st	rategy.		
	Volume Flow Rate		37.1	Specific Comments		No Load / Zero	
	at specified conditions           m3 / min         ft3 / min		Volume F		-	Flow Power	
	Below 0.5 Below 15		+/-		/0 +/- 8 +/- 7 +/- 10		
	0.5 to 1.5 15 to 50		+/-				
			+/-	5 +/-	6		
030.2			+/-	4 +/-	5		