	Federal Uniform			ir Compressors Not A	pplicable	
		Rotary Con MODEL DATA -	-	2		
1	Manufacturer:		FUNCOW	IF KESSED AIK		
1		Atlas Copco	<b>P</b> 10 1		07.00.0001	
	Model Number:	ZT 90 ST		Date:	07-22-2021	
2	Air-cooled	Water-co	ooled	Type:	Screw	
	Oil-injected	✓ Oil-free		# of Stages:	2	
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		5	503.1	(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			150.0	psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	150.8	psig*(c)	
6	Drive Motor Nominal Rating			120.7	hp	
7	Drive Motor Nominal Efficiency			96.2	percent	
8	Fan Motor Nominal Rating (if applicable)		ble)	0.0	hp	
9	Fan Motor Nominal Efficiency			91.7	percent	
10*	Total Package Input Power at Zero Flow*(e)		ow*(e)	26.8	kW*(e)	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			113.3	kW*(d)	
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			22.5	kW/100 cfm*(e)	
	*For models that are tested in t	he CAGI Performance V	erification Progra	am, these items are verified by pr	ogram administrator	
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.or a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.					
Member	<li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li>					
VCI		accordance with ISO 121 te "not significant" or "0		easurement of no load power equations of the second se	als less than 1%,	
ied Air & Gas Institute	<ul><li>d. Total package input p</li><li>e Tolerance is specified</li></ul>	oower at other than report d in ISO 1217, Annex E,	ted operating poin as shown in table	nts will vary with control strategy	τ.	
	Volume Flow Rate			Specific Energ	y No Load / Zero	
	at specified conditions		Volume Flo		Flow Power	
	<u>m3 / min</u>	<u>ft3 / min</u>	%	%		
	Below 0.5	Below 15	+/- 7		+/ 10	
	0.5 to 1.5	0.5 to 1.5 15 to 50   1.5 to 15 50 to 500			+/- 10	
030.2			+/- 5			