	Federal Uniform	n Test Method fo Rotary Cor		Air Compressors Not ixed Speed	Applicable
	Ν	MODEL DATA -	_	_	
1	Manufacturer:	Atlas Copco			
	Model Number:	ZT 145 S	TD-8.6	Dat	e: 01-05-2024
2	Air-cooled	cooled Water-cooled		Тур	e: Screw
	Oil-injected	✓ Oil-free		# of Stage	es: 2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		829.8	(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			124.7	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		ıre*(c)	124.7	psig*(c)
6	Drive Motor Nominal Rating			220.0	hp
7	Drive Motor Nominal Efficiency			95.8	percent
8	Fan Motor Nominal Rating (if applicable)		ble)	8.0	hp
9	Fan Motor Nominal Efficiency			87.6	percent
10*	Total Package Input	ge Input Power at Zero Flow*(e)		33.9	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			165.6	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			20.0	kW/100 cfm*(e)
	*For models that are tested in t	he CAGI Performance V	verification Progr	ram, these items are verified by	program administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.or a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.				
Member	b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.				
AGI ied Air & Gas Institute	manufacturer may stad. Total package input pe Tolerance is specified	te "not significant" or "(bower at other than repor l in ISO 1217, Annex E,)" on the test rep ted operating point as shown in tabl	nts will vary with control strat	
	Volume Flow Rate			Specific En	
	at specified c <u>m3 / min</u>	onditions <u>ft3 / min</u>	Volume Fl %	1	ion Flow Power
	Below 0.5	Below 15	70 +/-		
	0.5 to 1.5 15 to 50 1.5 to 15 50 to 500		+/-		+/- 10
			+/-	5 +/- 6	
030.2			+/-	4 +/- 5	