	rederal Unitor			Compressors Not Ap	opiicable	
		MODEL DATA -	npressor: Fixed			
1	Manufacturer:	Atlas Copco				
	Model Number:		-8.6	Date:	01-05-2024	
2	Air-cooled	Water-co	ooled	Туре:	Screw	
	Oil-injected	✓ Oil-free		# of Stages:	2	
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			1,526.0	(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			124.7	psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	124.7	psig*(c)	
6	Drive Motor Nominal Rating			348.7	hp	
7	Drive Motor Nominal Efficiency			96.2	percent	
8	Fan Motor Nominal Rating (if applicable)		ole)	10.7	hp	
9	Fan Motor Nominal Efficiency			81.3	percent	
10*	Total Package Input Power at Zero Flow*(e)		w*(e)	63.7	kW*(e)	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			305.2	kW*(d)	
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			20.0	kW/100 cfm*(e)	
	*For models that are tested in	the CAGI Performance V	erification Program, th	nese items are verified by pro	gram administrator	
Notes: Member	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions. b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured					
AGI	for this data sheet. c. No Load Power. In manufacturer may st d. Total package input	accordance with ISO 1217 ate "not significant" or "0 power at other than report	7, Annex E, if measure " on the test report. ed operating points wi	ement of no load power equal ill vary with control strategy.	s less than 1%,	
sed Air & Gas Institute	-	d in ISO 1217, Annex E, a power" and "energy" are s				
	Volume Flow Rate at specified conditions		Volume Flow Ra	Specific Energy Ate Consumption	No Load / Zero Flow Power	
	<u>m3 / min</u>	<u>ft3 / min</u>	%	%	Flow Fower	
	Below 0.5	Below 15	+/- 7	+/- 8		
	0.5 to 1.5 15 to 50		+/- 6	+/- 7	+/- 10	
030.2	1.5 to 15	1.5 to 15 50 to 500		+/- 6		
	Above 15	Above 15 Above 500 +		+/- 5		