	Federal Uniforr	n Test Method fo Rotary Con		Air Compressors Not 4 ixed Speed	Applicable
	I	MODEL DATA -	_	-	
1	Manufacturer:	Atlas Copco			
	Model Number:	ZT 55 ST	ГD-8.6	Date	: 01-05-2024
2	Air-cooled	Water-co	ooled	Туре	: Screw
	Oil-injected	✓ Oil-free		# of Stages	: 2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)		7	335.6	(acfm) *(a,e)
4	Full Load Operating Pressure*(b)			124.7	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		ire*(c)	124.7	psig*(c)
6	Drive Motor Nominal Rating			73.8	hp
7	Drive Motor Nominal Efficiency			95.8	percent
8	Fan Motor Nominal Rating (if applicable)		ble)	8.9	hp
9	Fan Motor Nominal Efficiency			91.7	percent
10*	Total Package Input	tal Package Input Power at Zero Flow*(e)		19.2	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			72.8	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			21.7	kW/100 cfm*(e)
	*For models that are tested in t	he CAGI Performance V	verification Progr	am, these items are verified by I	program administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.org   a. Measured at the discharge terminal point of the compressor package in accordance with   ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.				
Member	<ul><li>b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.</li><li>c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,</li></ul>				
AGI sed Air & Gas Institute	<ul><li>d. Total package input p</li><li>e Tolerance is specified</li></ul>	l in ISO 1217, Annex E,	ted operating poi as shown in tabl	nts will vary with control strates	gy.
	Volume Flow Rate at specified conditions		V I FI	Specific Ener	
	m3 / min	<u>ft3 / min</u>	Volume Fl %	1	n Flow Power
	Below 0.5   Below 15   +/     0.5 to 1.5   15 to 50   +/		+/- 7		
			+/-	6 +/- 7	+/- 10
			+/-	5 +/- 6	
030.2			4 +/- 5		