[Rot	COMPRESSOR DA Test Method for Certain tary Compressor: Variab ODEL DATA - FOR CO	Air Compressors Not A le Frequency Drive	pplicable
1	Manufacturer:	Atlas Copco		
	Model Number:	ZT 145 VSD+-10.4	Date:	01-06-2024
2	✓ Air-cooled		Туре:	Screw
	Lubricated	✓ Oil-free	# of Stages:	2
3	Full Load Operating P	ressure*(b)	150.0	psig*(b)
4	Drive Motor Nominal Rating		100.6 & 100.6	hp
5	Drive Motor Nominal Efficiency		97.0 & 97.0	percent
6	Fan Motor Nominal Rating (if applicable)		11.8	hp
7	Fan Motor Nominal Efficiency		69.9	percent
8*	Input Power (kW)		Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)
	157.5 Max		750.8	21.0
	126.2		603.5	20.9
	98.2		456.2	21.5
	72.0		308.9	23.3
	45.8 Min		161.5	28.3
9*	Total Package Input	Power at Zero Flow*(c,d)	0.0	kW
10	Specific Power (kW/100ACFM) 12			
	~			
	~	200 Caj	400 600 pacity (ACFM)	800
*For mo Notes: Member	odels that are tested in the CA Consult CAGI website for a a. Measured at the discha ISO 1217, Annex E; a b. The operating pressure c. No Load Power. In ac manufacturer may statu d. Tolerance is specified	GI Performance Verification Prr list of participants in the third pa rge terminal point of the compressor packa fm is actual cubic feet per minute at inlet c at which the Capacity and Electrical Conss cordance with ISO 1217, Annex E, if meass e "not significant" or "0" on the test report. in ISO 1217, Annex E, as shown in table be	ogram, these items are verified l arty verification program: uge in accordance with conditions. umption were measured for this data sheet. urement of no load power equals less than elow:	oy program administrator www.cagi.org
Notes:	odels that are tested in the CA Consult CAGI website for a a. Measured at the discha ISO 1217, Annex E; ac b. The operating pressure c. No Load Power. In ac manufacturer may statu d. Tolerance is specified NOTE: The terms "po Volume F	GI Performance Verification Pr list of participants in the third pa rge terminal point of the compressor packa fm is actual cubic feet per minute at inlet c at which the Capacity and Electrical Conss cordance with ISO 1217, Annex E, if meas "not significant" or "0" on the test report. in ISO 1217, Annex E, as shown in table bo wer" and "energy" are synonymous for pur low Rate	ogram, these items are verified la arty verification program: use in accordance with conditions. umption were measured for this data sheet urement of no load power equals less than elow: poses of this document. Specific Energy	by program administrator www.cagi.org 1%, No Load / Zero
Notes:	odels that are tested in the CA Consult CAGI website for a a. Measured at the discha ISO 1217, Annex E; as b. The operating pressure c. No Load Power. In ac manufacturer may statu d. Tolerance is specified NOTE: The terms "po	GI Performance Verification Pr list of participants in the third pa rge terminal point of the compressor packa fm is actual cubic feet per minute at inlet c at which the Capacity and Electrical Conss cordance with ISO 1217, Annex E, if meas "not significant" or "0" on the test report. in ISO 1217, Annex E, as shown in table bo wer" and "energy" are synonymous for pur low Rate	ogram, these items are verified l arty verification program: use in accordance with conditions. umption were measured for this data sheet. urement of no load power equals less than elow: poses of this document.	by program administrator www.cagi.org 1%,
Notes:	odels that are tested in the CA Consult CAGI website for a a. Measured at the discha ISO 1217, Annex E; ac b. The operating pressure c. No Load Power. In ac manufacturer may statu d. Tolerance is specified NOTE: The terms "po Volume F at specified	Cal AGI Performance Verification Pri- list of participants in the third parge terminal point of the compressor packa fm is actual cubic feet per minute at inlet c at which the Capacity and Electrical Conssi cordance with ISO 1217, Annex E, if meass "not significant" or "0" on the test report. in ISO 1217, Annex E, as shown in table bo wer" and "energy" are synonymous for pur low Rate conditions Volum	ogram, these items are verified la arty verification program: use in accordance with conditions. umption were measured for this data sheet. urement of no load power equals less than elow: poses of this document. specific Energy consumption	by program administrator www.cagi.org 1%, No Load / Zero
Notes:	odels that are tested in the CA Consult CAGI website for a a. Measured at the discha ISO 1217, Annex E; ac b. The operating pressure c. No Load Power. In ac manufacturer may state d. Tolerance is specified NOTE: The terms "po Volume F at specified <u>m3/min</u>	Cal AGI Performance Verification Pre- list of participants in the third parge terminal point of the compressor packa offm is actual cubic feet per minute at inlet or at which the Capacity and Electrical Const e "at which the Capacity and Electrical Const e "not significant" or "0" on the test report. in ISO 1217, Annex E, as shown in table be wert" and "energy" are synonymous for pur- low Rate conditions Volum <u>ft3/min</u>	ogram, these items are verified I arty verification program: ge in accordance with conditions. umption were measured for this data sheet. urement of no load power equals less than elow: poses of this document. me Flow Rate Consumption % %	by program administrator www.cagi.org 1%, No Load / Zero