[COMPRESSOR DA Federal Uniform Test Method for Certain Rotary Compressor: Variab MODEL DATA - FOR CO	Air Compressors Not Aj le Frequency Drive	pplicable
1	Manufacturer: Atlas Copco	MI RESSED AIR	
	Model Number: ZT 250 VSD-10.4	Date:	01-06-2024
2	✓ Air-cooled	Туре:	Screw
_	Lubricated Voil-free	# of Stages:	2
3	Full Load Operating Pressure*(b)	# 61 Stages: 150.0	
4	Drive Motor Nominal Rating	335.3	psig*(b) hp
5	Drive Motor Nominal Efficiency	95.2	percent
6	Fan Motor Nominal Rating (if applicable)	9.4	hp
7	Fan Motor Nominal Efficiency	82.0	percent
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)
	278.6 Max	1,265.7	22.0
	257.6	1,169.0	22.0
	237.8	1,072.3	22.2
	219.1	975.6	22.5
	200.9 Min	878.9	22.9
9*	Total Package Input Power at Zero Flow*(c,d)	34.1	kW
10	Specific Power (kw/100ACFM) 12 12	• ••••	-•
	10 0 200 400 600		00 1400
*For m	0 200 400 600	pacity (ACFM)	
*For m Notes: Member	0 200 400 600 Cap odels that are tested in the CAGI Performance Verification Pro Consult CAGI website for a list of participants in the third pa a. Measured at the discharge terminal point of the compressor packag ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet or b. The operating pressure at which the Capacity and Electrical Consu c. No Load Power. In accordance with ISO 1217, Annex E, if measu manufacturer may state "not significant" or "0" on the test report. d. Tolerance is specified in ISO 1217, Annex E, as shown in table be	bacity (ACFM) ogram, these items are verified l arty verification program: ge in accordance with onditions. Imption were measured for this data sheet. Irrement of no load power equals less than low:	by program administrator www.cagi.org
Notes:	0 200 400 600 Cap odels that are tested in the CAGI Performance Verification Pro Consult CAGI website for a list of participants in the third pa a. Measured at the discharge terminal point of the compressor packag ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet or b. The operating pressure at which the Capacity and Electrical Consu c. No Load Power. In accordance with ISO 1217, Annex E, if meast manufacturer may state "not significant" or "0" on the test report. d. Tolerance is specified in ISO 1217, Annex E, as shown in table be NOTE: The terms "power" and "energy" are synonymous for purp Volume Flow Rate	bacity (ACFM) ogram, these items are verified l arty verification program: ge in accordance with onditions. Imption were measured for this data sheet. Irrement of no load power equals less than low: boses of this document. Specific Energy	by program administrator www.cagi.org
Notes:	0 200 400 600 Cap odels that are tested in the CAGI Performance Verification Pro Consult CAGI website for a list of participants in the third pa a. Measured at the discharge terminal point of the compressor packag ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet co b. The operating pressure at which the Capacity and Electrical Consu c. No Load Power. In accordance with ISO 1217, Annex E, if meast manufacturer may state "not significant" or "0" on the test report. d. Tolerance is specified in ISO 1217, Annex E, as shown in table be NOTE: The terms "power" and "energy" are synonymous for purp Volume Flow Rate	bacity (ACFM) ogram, these items are verified l rrty verification program: ge in accordance with onditions. Imption were measured for this data sheet. Irrement of no load power equals less than low: poses of this document.	by program administrator www.cagi.org
Notes:	0 200 400 600 Cap odels that are tested in the CAGI Performance Verification Pro Consult CAGI website for a list of participants in the third pa a. Measured at the discharge terminal point of the compressor packag ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet co b. The operating pressure at which the Capacity and Electrical Consult consult CAGI webwer. In accordance with ISO 1217, Annex E, if meast manufacturer may state "not significant" or "0" on the test report. d. Tolerance is specified in ISO 1217, Annex E, as shown in table be NOTE: The terms "power" and "energy" are synonymous for purp Volume Flow Rate at specified conditions Volum	bacity (ACFM) bgram, these items are verified l rty verification program: ge in accordance with onditions. Imption were measured for this data sheet. Irrement of no load power equals less than low: boses of this document. Specific Energy Consumption	by program administrator www.cagi.org
Notes:	0 200 400 600 Cap odels that are tested in the CAGI Performance Verification Pro Consult CAGI website for a list of participants in the third par a. Measured at the discharge terminal point of the compressor package ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet or b. The operating pressure at which the Capacity and Electrical Consult c. No Load Power. In accordance with ISO 1217, Annex E, if meast manufacturer may state "not significant" or "0" on the test report. d. Tolerance is specified in ISO 1217, Annex E, as shown in table be NOTE: The terms "power" and "energy" are synonymous for purp Volume Flow Rate Volum at specified conditions Volum	bacity (ACFM) bgram, these items are verified I arty verification program: ge in accordance with onditions. umption were measured for this data sheet. trement of no load power equals less than low: boses of this document. by the Flow Rate by th	by program administrator www.cagi.org