	Federal Uniform	m Test Method fo		r Compressors Not A	pplicable
			npressor: Fix	-	
	-	MODEL DATA -	FOR COM	PRESSED AIR	
1	Manufacturer: Atlas Copco				
	Model Number: ZT 145 STD-10.4		STD-10.4	Date:	07-01-2020
2	Air-cooled	Water-co	ooled	Type:	Screw
	Oil-injected	✓ Oil-free		# of Stages:	2
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			749.6	(acfm) *(a,e)
4	Full Load Operating	ll Load Operating Pressure*(b)		135.0	psig*(b)
5	Maximum Full Flow Operating Pressure*(c)		re*(c)	150.8	psig*(c)
6	Drive Motor Nominal Rating			220.0	hp
7	Drive Motor Nominal Efficiency			95.8	percent
8	Fan Motor Nominal Rating (if applicable)		ole)	8.0	hp
9	Fan Motor Nominal Efficiency			87.6	percent
10*	Total Package Input	otal Package Input Power at Zero Flow*(e)		41.3	kW*(e)
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			154.8	kW*(d)
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			20.7	kW/100 cfm*(e)
	*For models that are tested in	the CAGI Performance V	erification Program	n, these items are verified by pro	ogram administrator
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.o a. Measured at the discharge terminal point of the compressor package in accordance with www.cagi.o				
Member	ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.				
	c. No Load Power. In	accordance with ISO 1217 ate "not significant" or "0		surement of no load power equa	ls less than 1%,
d Air & Gas Institute	 d. Total package input e Tolerance is specifie 	power at other than report d in ISO 1217, Annex E, a	ed operating point as shown in table l	s will vary with control strategy below:	
	NOTE: The terms "power" and "energy" are synonymous fo Volume Flow Rate		ynonymous for pe	Specific Energy	No Load / Zero
	at specified conditions		Volume Flow	v Rate Consumption	Flow Power
	<u>m3 / min</u> <u>ft3 / min</u>		%	%	+/- 10
	Below 0.5	Below 15		+/- 8	
	0.5 to 1.5			+/- 7	
030.2			+/- 5	+/- 6	
.50.2	Above 15 Above 500 +/-		+/- 4	+/- 5	