	Federal Unifor		SSOR DATA SI or Certain Air C	HEET Compressors Not Aj	oplicable	
		Rotary Cor	npressor: Fixed	Speed		
		MODEL DATA -	FOR COMPR	ESSED AIR		
1	Manufacturer:	Atlas Copco				
	Model Number	: ZT 145	-10.4	Date:	08-10-2021	
2	Air-cooled	Water-co	poled	Type:	Screw	
	☐ Oil-injected			# of Stages:	2	
3*	Rated Capacity at Full Load Operating Pressure*(a,e)			749.7	(acfm) *(a,e)	
4	Full Load Operating Pressure*(b)			150.0	psig*(b)	
5	Maximum Full Flow Operating Pressure*(c)			150.8	psig*(c)	
6	Drive Motor Nominal Rating			220.0	hp	
7	Drive Motor Nominal Efficiency			95.8	percent	
8	Fan Motor Nominal Rating (if applicable)		ble)	8.0	hp	
9	Fan Motor Nominal Efficiency			87.6	percent	
10*	Total Package Input Power at Zero Flow*(e)		ow*(e)	30.1	kW*(e)	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure*(d)			161.4	kW*(d)	
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure*(e)			21.5	kW/100 cfm*(e)	
:	*For models that are tested ir	the CAGI Performance V	verification Program, th	ese items are verified by pro	gram administrator	
Notes:	Consult CAGI website for a list of participants in the third party verification program: www.cagi.c a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.					
Member	b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.					
VU		c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.				
AUI sed Air & Gas Institute	 d. Total package input e Tolerance is specifi 	0	ted operating points will as shown in table below			
	Volume Flow Rate			Specific Energy	No Load / Zero	
	at specified conditions		Volume Flow Ra		Flow Power	
	<u>m3 / min</u>	<u>ft3 / min</u>	%	%		
	Below 0.5 Below 15		+/-7 +/-8		+/- 10	
	0.5 to 1.5 15 to 50		+/- 6 +/- 7 +/- 5 +/- 6			
	1.5 to 15	50 to 500 +/ Above 500 +/		+/- 6 +/- 5		