

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Atlas Copco														
2	Model Number: ZT 90 VSD STD-8.6	Date: 07-01-2020													
	<input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled	Type: Screw													
	<input type="checkbox"/> Lubricated <input checked="" type="checkbox"/> Oil-free	# of Stages: 2													
3	Full Load Operating Pressure*(b)	105.0	psig*(b)												
4	Drive Motor Nominal Rating	120.7	hp												
5	Drive Motor Nominal Efficiency	95.0	percent												
6	Fan Motor Nominal Rating (if applicable)	8.0	hp												
7	Fan Motor Nominal Efficiency	87.6	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	Max	529.1	19.0												
		449.7	19.3												
		370.3	19.8												
	Min	290.9	21.0												
9*	Total Package Input Power at Zero Flow*(c,d)	19.8	kW												
10	<table border="1" style="margin: 10px auto; border-collapse: collapse;"> <caption>Graph Data Points</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr><td>210</td><td>23.5</td></tr> <tr><td>290.9</td><td>21.0</td></tr> <tr><td>370.3</td><td>19.8</td></tr> <tr><td>449.7</td><td>19.3</td></tr> <tr><td>529.1</td><td>19.0</td></tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	210	23.5	290.9	21.0	370.3	19.8	449.7	19.3	529.1	19.0
Capacity (ACFM)	Specific Power (kW/100ACFM)														
210	23.5														
290.9	21.0														
370.3	19.8														
449.7	19.3														
529.1	19.0														

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	