

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Atlas Copco														
2	Model Number: ZR 55 FLX-8.6 VSD	Date: 07-08-2025													
	☐ Air-cooled ☒ Water-cooled	Type: Tooth													
	☐ Lubricated ☒ Oil-free	# of Stages: 2													
3	Full Load Operating Pressure*(b)	124.7	psig*(b)												
4	Drive Motor Nominal Rating	40.2 & 40.2	hp												
5	Drive Motor Nominal Efficiency	96.3 & 96.3	percent												
6	Fan Motor Nominal Rating (if applicable)	2.6	hp												
7	Fan Motor Nominal Efficiency	59.0	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	66.2 Max	297.8	22.2												
	53.2	242.8	21.9												
	40.1	187.9	21.3												
	29.7	132.9	22.3												
	19.0 Min	78.0	24.4												
9*	Total Package Input Power at Zero Flow*(c,d)	0.0	kW												
10	<table border="1"> <caption>Specific Power vs Capacity Data</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>24.5</td> </tr> <tr> <td>135</td> <td>22.5</td> </tr> <tr> <td>190</td> <td>21.5</td> </tr> <tr> <td>245</td> <td>22.2</td> </tr> <tr> <td>300</td> <td>22.5</td> </tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	75	24.5	135	22.5	190	21.5	245	22.2	300	22.5
Capacity (ACFM)	Specific Power (kW/100ACFM)														
75	24.5														
135	22.5														
190	21.5														
245	22.2														
300	22.5														

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	