The LSV39 range





THE GAME CHA

The Game changing LSV39 will re-write the industry standards! We made the impossible possible and designed the most powerful vane grinder for it size on the market. With the incredible 2,4 hp, in a small size, we are stepping up the game and allowing our customers to be even more productive. Whatever your requirements – you'll find your next tool in the **39-series**. **The LSV 39-series** is truly meeting with popular demand, giving you new opportunities in rough grinding, de-burring and sanding in cramped, narrow spaces.

New ergonomic trigger that reduces the total grip size.


Worlds highest power to weight ratio for it's size of vane grinders! 2,4 hp lubrication free motor means a higher productivity and shortened process time for you.

Improved life-time of the angle gear to an amazing 2500h service life.

Spindle lock for quick and easy change of grinding wheel.

New ergonomic support handle helps improving the working conditions for the operator.





Power at different hose lengths 5" angle grinder.

Three ways to a shorter production process

Longer service life

The new, extra durable angle gear is nearly maintenance free, ensuring you many years of excellent function. All it needs is a grease change every 1,000 hrs of use and we guarantee 2,500 hrs of service life. All 39-series angle grinders and sanders have sealed angle heads ensuring long service intervals.

More power – more productivity

Atlas Copco's LSV 39 provides over 50% higher output than many other grinders on the market, and is the most powerful grinder in it's size. This has been accomplished with an all new air-motor. The increased power translates directly into higher rate of material removal and improved productivity. Compared to the old LSV38 it will increase your productivity with up to 20%. It almost does the job for you!

The efficiency of the air motor ensures consistent performance, even when the grinder is connected to a long hose. With 2,4 hp output at 10 feet hose length, you still get good output with a much longer hose.

Ergonomic design – less strain on the operator

Good ergonomics characterizes the 39-series, to help reduce operator stress and fatigue. All models in the 39-series have textured non-slip grips that are comfortable to hold.





Piped away rear exhaust leaves you with a cleaner working environment.

LSV 39 sander – excellent control

The LSV 39 sander is a great choice for both fine and rough sanding applications. The comfortable support handle gives you excellent control during the sanding process. The lube-free motor keeps the sanded surface nice and oil-free.



LSV 39 with dust extraction

All version of LSV 39 sanders can be equipped with accessories for efficient extraction of sanding dust. This is the perfect solution for sanding operationsin e.g glass fiber re-inforced plastic and similar materials.

Technical data

| | | Max output hp | Max wheel/ pad dia inch | Weight Ibs | Spindle thread | Spindle length inch | Air consumption at | | | | |
|----------------|-------------------------------|------------------|----------------------------------|---------------|-------------------|---------------------------|-----------------------|----------------------|-----------------------------|-------------------------|--------------|
| Model | Max free speed r/min | | | | | | max output cfm | free speed cfm | Rec hose size inch | Air inlet thread NPT | Ordering No. |
| Angle grinder | | | | | | | | | | | |
| LSV39 S12-527 | 12000 | 2.4 | 5" | 4.0 | UNC 5/8" | 0.83 | 63 | 37 | 5/8" | 3/8" | 8423 0133 02 |
| Angle sander | | | | | | | | | | | |
| LSV39 S066-5/8 | 6600 | 2.15 | 7" | 3.5 | UNC 5/8" | 1.38 | 54.3 | 24 | 5/8" | 3/8" | 8423 0133 05 |
| LSV39 S085-5/8 | 8500 | 2.4 | 7" | 3.5 | UNC 5/8" | 1.38 | 61.1 | 33.7 | 5/8" | 3/8" | 8423 0133 03 |
| LSV39 S120-5/8 | 12000 | 2.4 | 5" | 3.5 | UNC 5/8" | 1.38 | 63 | 37 | 5/8" | 3/8" | 8423 0133 07 |

Accessories

| | LSV39 | | | | | | |
|--|--------------|--|--|--|--|--|--|
| Hand shield Ø 5-7" for sanders, standard | 4150 1936 80 | | | | | | |
| Hand shield Ø 5-7" for sanders, robust | 4150 1941 80 | | | | | | |
| Spot suction for diamond cutting wheel | | | | | | | |
| Ø 5" (cutting depth 1 3/16") | 3780 4008 74 | | | | | | |
| Diamond cutting wheel Ø 5" | 3780 5074 61 | | | | | | |
| Spot suction for sanding with fibre disc | | | | | | | |
| Ø 5" kit | 3780 4008 85 | | | | | | |
| Ø 7" kit | 3780 4008 84 | | | | | | |
| Add on spot suction kit | | | | | | | |
| Ø 7" kit (for depressed center wheel) | 3780 4032 14 | | | | | | |
| MultiFlex | 8202 1350 28 | | | | | | |



Join the revolution at:



Committed to sustainable productivity



www.atlascopco.com